

## Key performance

 Specifically desidgned to absorb the mechanical vibrations caused by new generation of printing presses

vulcan Techno

- Implements all benefits of the **Dynatech System:** 
  - Better vibration absorption
  - · Less gears streaking marks
  - Higher paper smash resistance
  - Blanket consistency
  - Excellent reboundability

## **MAIN APPLICATION**

Commercial Web Heatset

Vulcan Techno is available in 3-ply, (1,70 mm) thickness.



**Vulcan Techno** 

## The product at a glance

INK COMPATIBILITY	Hybrid
PRINTING SURFACE COLOUR	Green
THICKNESS (mm)	1,70
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
SURFACE ROUGHNESS (Ra micron)	0,8
FEED FEATURES	Positive
ELONGATION (%)	<0,9
TENSILE STRENGHTS (N/mm)	>60
WATER & SOLVENT PROTECTION	Yes
NEW TECHNOLOGY	Dynatech
ADDITIONAL INFORMATION	
DYNATECH SYSTEM	Special rubber compound used for the compressible layer

FOR ANY FURTHER DETAILS AND FOR A QUOTATION PLEASE REFER TO YOUR SALES MANAGER OR EMAIL US AT: printing@trelleborg.com